
E-max - High Damage Threshold 800 nm Ultrafast Laser Mirrors for 0° Incidence

These high performance mirrors are intended to deliver very high damage resistance for general purpose beam steering tasks in Ti:S ultrafast laser based applications.

Advantages

- Superior damage resistance
- Wide spectral bandwidth
- Minimal group velocity dispersion
- High reflectivity
- Excellent mechanical durability

Common Specifications		
Chamfer	0.50 mm at 45°	
Clear Aperture	85%	
Diameter Tolerance	+0.00, -0.13 mm	
Front Surface Flatness	λ/10 at 633 nm	
Material	Fused Silica	
Rear Surface	Commercial Polish	
Surface Quality	10-5	
Thickness Tolerance	±0.25 mm	
Wedge	<5 arc minutes	
Surface 1 Flatness	λ/10 at 633 nm	
Surface 1 Surface Quality	10-5	
Surface 1 Coating	≥99.5% reflectivity at 800 nm	
Surface 1 Angle Of Incidence	0°	
Surface 2 Flatness	Commercial polish	
Surface 2 Surface Quality	Commercial polish	
Surface 2 Coating	None	



Part Number	Diameter	Thickness	Price
MR6220	25.4	9.525	\$190.00
MR6260	50.8	9.525	\$295.00

